PATENT ABSTRACTS OF JAPAN

(11)Publication number:

07-167340

(43) Date of publication of application: 04.07.1995

(51)Int.CI.

F16K 41/04

F16J 15/24

(21)Application number : **05-343356**

(71)Applicant: KITZ CORP

(22)Date of filing:

17.12.1993


(72)Inventor: NAKANISHI SADAYUKI

(54) SHAFT SEALING DEVICE VALVE

(57)Abstract:

PURPOSE: To more tightly fasten a packing by making a push-pressing taper part which is formed on the top end part of the push-pressing member of a connecting flange abut on the taper surface of a gland, and activating wedge action so as to press the gland downward.

CONSTITUTION: A shaft mounting part 6 for penetrating a stem 10 is formed upward the center part of a body part 1a, and a packing chamber 7 in which space is formed around the stem 10 is formed upward the shaft mounting part 6. A gland 9 for push-pressing a packing 8 from upward is provided upward the packing chamber 7 so as to more fasten the packing 8. On a connecting flange 11, a screw part 12 is formed as an inserting part



from a side surface toward the axial core of the stem 10, and a push bolt 13 as a pushpressing member is inserted in the screw part 12 so as to face of the gland 9. A pushpressing taper part 13a is formed on the top end part of the push bolt 13, and also a taper surface 9a is formed on the upper surface of the gland 9 which abuts thereon. Force which is applied by the push bolt 13 is push-pressed in axial core direction.

LEGAL STATUS

135

197

[Date of request for examination]

02.03.1998

[Date of sending the examiner's decision of

rejection]

[Kind of final disposal of application other than

the examiner's decision of rejection or

application converted registration]

[Date of final disposal for application]

[Patent number]

3154265

[Date of registration]

02.02.2001

[Number of appeal against examiner's

decision of rejection]

[Date of requesting appeal against examiner's

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office